

Slip-resistant care

FINISH CARE STOP

Water-based and slip-resistant care emulsion for initial and maintenance care on sealed wood and cork floors, linoleum, natural and artificial stone floors.

PRODUCT DESCRIPTION:

This product has been specially developed to take into account the particular requirements of DIN 18032. We recommend this slip resistant care product for: sports halls, homes for the elderly, kindergartens, public buildings. In addition, the appearance of the surface will be improved and at the same time the life time of the floor is extended.

SUITABLE FOR:

- ▶ sealed wood/cork floors
- ▶ sealed multilayer wood floors
- ▶ Linoleum
- ▶ PVC
- ▶ natural and synthetic stone floors



APPLICATION:

1. Before use, the container must be brought to room temperature (20 °C) and must be shaken well.
2. **Initial care:** Apply a thin, even coat of PALLMANN FINISH CARE STOP using a PALLMANN FLOOR MOP. Apply undiluted product at a rate of 20 ml per square metre. No buffing is required.
3. **Maintenance care:** Carry out routine cleaning with PALLMANN CLEAN. Afterwards dilute approx. 50 - 150 ml PALLMANN FINISH CARE STOP with 5 litres of water and apply thinly with a PALLMANN FLOOR MOP. The maintenance care should be carried out as required.
4. After drying (approx. 1 hours) the surface can be put back into use.
5. On thoroughly cleaned floors (PALLMANN CLEAN STRONG) we recommend an initial care with PALLMANN FINISH CARE.
6. The exact maintenance and care routine is shown in the respective care instruction.

PRODUCT BENEFITS / PROPERTIES:

- ▶ fast drying
- ▶ hard wearing
- ▶ slip resistant
- ▶ no polishing required

TECHNICAL DATA:

Packaging:	plastic container
Packsize:	0,75 and 10 l
Consumption:	Initial care: pure - approx. 20 ml/m² Maintenance care: approx. 50 - 150 ml/5 l water
Working climate:	between 18 – 25 °C and 35 – 65 % relative humidity

SURFACE PREPARATION:

Remove traces of dirt and dust by using the PALLMANN MOP, broom or vacuum cleaner.

IMPORTANT NOTES:

- ▶ Optimum temperature is 18 to 25 °C with the relative humidity > 35 % and < 65 %. Low temperatures and high humidity will extend the drying time. High temperatures and low humidity will shorten the drying time.
- ▶ Shelf life minimum 24 months in original packaging when stored in dry conditions. Protect from freezing and do not expose to temperatures over 40 °C.
- ▶ Tightly reseal opened containers.
- ▶ When using our care products, especially on factory finished floors, and in rare cases there may be some appearance differences. We therefore recommend to create a small sample area in advance to check compatibility.
- ▶ Leave freshly sealed surfaces until fully hardened before treating with PALLMANN FINISH CARE STOP.
- ▶ Regular maintenance with PALLMANN FINISH CARE STOP improves the appearance and increases the wear life of the sealed surface.
- ▶ The following standards and notices are applicable and especially recommended: DIN 18356 "Working with parquet and woodblocks", DIN 18365 "Working with floor coverings".

PROTECTION OF THE WORKPLACE AND THE ENVIRONMENT:

Not flammable. Use of barrier cream and ventilation of the work area are recommended.

DISPOSAL:

Do not allow dispersal into drains, sewers or ground. Rinse containers, which have been emptied from any residues, with little water and dispose of the containers in accordance with local guidelines as recyclable packaging. Collect and reuse rinsing water and product remnants. If even necessary, dispose of containers with residues as well as product remnants as special waste.