

TECHNICAL DATA SHEET

Water-based adhesive for gilding



UZIN MIXION M-60

Gilding adhesive for interior use on wood, clay and/or stucco

Applications:

Water-soluble mixion adhesive for consolidate gold/silver leaf on hagiographies and/or handicrafts. Indoor use only.

Recommended product for:

- ▶ for gold/silver leaf fixation
- ▶ for gold/silver imitation leaf fixation

Product benefits / features:

UZIN MIXION M-60 is a water-soluble adhesive for bonding gold/silver foils on painted surfaces such as wood, gesso, etc. Gold/silver foils can be glued after 10 minutes (open time). It is applied on surfaces that are not waterproof with dabbing movements, either with a brush or by spraying. Can be diluted up to 10-30% with water.

Protection of the workplace and the environment:

No Solvents. Non-flammable. Keep away from children. Avoid eye contact. Ventilation of the work area is recommended. Once completely dry, the product presents no physiological or ecological hazard. Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). **Information for persons with allergies is available at +30 210 7793777 (Greece).**

Disposal:

Collect and reuse product scraps where possible. Do not discharge into drains, surface water or soil. Empty plastic containers after being cleaned and scraped of residue can be recycled. Containers of dried residues are classified as household/construction solid waste.

Technical Data:

Package:	PE container PE 1kg and 5kg
Storage:	minimum 12 months
Color:	White/transparent
Consumption:	100-120 gr/m ²
Open time:	15-30 min
Application:	By hand, brush, or spray

* At 20°C and 65% R.H.

UZIN Hellas Polychimiki G. Matziaris S.A. operates a quality assurance system which conforms to the EN ISO 9001/2008 standard. This has been certified by ESYP Greece and TÜV Germany. Accordingly, all products and services meet the specifications laid down in this system. As individual circumstances and working practices are unknown, UZIN Hellas accepts no liability for any damage resulting from the use of any of its products. The above information is based on our experience and careful investigations. The variety of associated materials and different construction and working conditions cannot be individually checked or influenced by us. The quality of your work depends, therefore, on your own professional judgement and product usage. The publication of this Product Data Sheet invalidates all previous Product Information 21/11/2022

