

UZIN NITROU

Organic solvent mixture for surface cleaning and color paint dilution

Applications:

UZIN NITROU is a mixture of drastic but no dangerous organix solvents, that removes color paints and varnishes from various surfaces e.g. wood, metal, ceramic etc. It does not corrode nor discolorate the applied surfaces.

Recommended product for:

- ▶ Remove of paints and varnishes made from alkyd, epoxy, or polyurethane resins.
- ▶ Cleaning tools and accessories from residues of adhesives, paints and enamel colors and other products that cannot be cleaned with water.

Product benefits / features:

Mixture of active organic solvents for color paints and varnishes removal.

- ▶ Deep stripping
- ▶ Wide range of applications
- ▶ Does not cause corrosion
- ▶ Does not contain trichlorethylene

Ask and study carefully Safety Data Sheet of the product

Technical Data:

Package:	Tin cans 1kg,5kg, 19kg & barrel 180Kg
Storage:	minimum 6 months
Color:	Transparent
Consumption:	Depends on the application
Density:	840,72g/l ^t
Dynamic viscosity:	0,515 cP (20°C)
VOC:	840,72g/l ^t
Vapor pressure:	53,16 mm Hg (20°C)
Boiling point:	96,33° C

* At 20°C and 65% R.H.

Important notes:

- ▶ Shelf life minimum 6 months in original packaging when stored in cool, dry conditions. Carefully and tightly seal opened containers and use the contents as quickly as possible.
- ▶ Optimum working conditions are 5-30°C.

Protection of the workplace and the environment:

High solvent content. Highly flammable. Irritant. Avoid skin contact with liquid product. Solvents in this product may form explosive air-vapor-mixture. Therefore provide good ventilation during and after use. No smoking, no open flames. Do not inhale vapors. Switch off all electric devices like door-bells, refrigerators, electric stoves, etc. Use barrier cream and protective gloves. Observe safety information on product label as well as safety data sheet **Information for persons with allergies is available at +30 210 7793777 (Greece).**

Disposal:

Collect product residues wherever possible and reuse. Do not allow to enter the sewer system, bodies of water or the soil. Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. Empty metal cans could be reused.