

UZIN POLY-ACET

Organic solvent based on acetone

Applications:

UZIN POLY-ACET is an acetonic solvent, that removes color paints and varnishes from various surfaces e.g. wood, metal, ceramic etc. It does not corrode nor discolorate the applied surfaces.

Recommended product for:

- ▶ Remove of paints and varnishes made from acryl and alkyd resins.
- ▶ Diluting neoprene adhesives
- ▶ Cleaning tools and accessories from residues of adhesives, paints and enamel colors and other products that cannot be cleaned with water.

Product benefits / features:

Organic solvent for color paints and varnishes removal and diluting.

- ▶ Deep stripping
- ▶ Wide range of applications
- ▶ Does not cause corrosion

Ask and study carefully Safety Data Sheet of the product

UZIN Hellas Polychimiki G. Matziaris S.A. operates a quality assurance system which conforms to the EN ISO 9001/2008 standard. This has been certified by ESXD Greece and TÜV Germany. Accordingly, all products and services meet the specifications laid down in this system. As individual circumstances and working practices are unknown, UZIN Hellas accepts no liability for any damage resulting from the use of any of its products. The above information is based on our experience and careful investigations. The variety of associated materials and different construction and working conditions cannot be individually checked or influenced by us. The quality of your work depends, therefore, on your own professional judgement and product usage. The publication of this Product Data Sheet invalidates all previous Product Information 02/11/2022



Technical Data:

Package:	Tin cans 1kg, 5kg, 17kg
Storage:	minimum 6 months
Color:	Transparent
Consumption:	Depends on the application
Density:	791,48g/lit
Dynamic viscosity:	0,32cP (20°C)
VOC:	791,48g/lit
Vapor pressure:	183,3 mm Hg (20° C)
Boiling point:	56,3°C

* At 20°C and 65% R.H.

Important notes:

- ▶ Shelf life minimum 6 months in original packaging when stored in cool, dry conditions. Carefully and tightly seal opened containers and use the contents as quickly as possible.
- ▶ Optimum working conditions are 5-30°C.

Protection of the workplace and the environment:

Causes serious eye irritation. Highly flammable liquid and vapour. May cause drowsiness or dizziness. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of fire: Use ABC powder extinguisher to extinguish. Repeated exposure may cause skin dryness or cracking. **Information for persons with allergies is available at +30 210 7793777 (Greece).**

Disposal:

Collect product residues wherever possible and reuse. Do not allow to enter the sewer system, bodies of water or the soil. Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. Empty metal cans could be reused.