

UZIN RM-35

Dispersion joint adhesive (D3) for bonding tongue and groove joints

Description:

Dispersion joint adhesive for tongue and groove joints in:

- ▶ Pre-finished wood flooring
- ▶ Laminate flooring
- ▶ Chipboard

Also suitable as a multipurpose wood glue for a wide range of woods and wood materials, for gluing joints, plugs and dowels, etc.

Product properties/benefits:

Ready to use, high viscosity, water-based, white dispersion adhesive in a practical applicator bottle.

Composition: Poly vinyl acetate

- ▶ Rapid drying / dries transparent
- ▶ High final strength
- ▶ Semi-rigid / flexible
- ▶ Good water-resistance
- ▶ Classification D3
- ▶ Solvent-free

Technical specifications:

Packaging:	Plastic bucket PE
Sizes:	1, 5 and 15kg
Storage:	min. 12 months
Color:	beige
Consumption:	800 –1200 g/m ²
Working temperature:	min. 15°C at ground level
Working time:	approx. 30 minutes*
Ready for load-bearing:	After 2 –3 days*
Grinding:	After adhesive has cured

* At 20 °C and 65% relative humidity.

Consumption:

Consumption (acc. to size of joint)	5- 30 g / lin. m.
810 g bottle is sufficient for	approx. 25-150 lin.m.

Substrate preparation:

The surface must be sound, dry, absorbent, clean and free from materials that would impair adhesion.

Application

- ▶ Cut off the tip of the nozzle at an angle to give the required size of opening.
- ▶ Apply adhesive to the upper surface of the tongue or into the groove. Then push the wood components together within the open time and, if necessary, knock together with a mallet or hammer.
- ▶ If the correct quantity is applied, a small amount of glue will squeeze out of the joint.
- ▶ With pre-finished wood flooring and laminate flooring, immediately wipe off any excess adhesive with a damp cloth.

Important notes:

- ▶ Shelf-life minimum 12 months in original container when stored in relatively cool conditions. Protect from frost.
- ▶ Optimum working conditions are 18-25 °C/ 64-77 °F, relative humidity < 75%

Protection of the workplace and the environment:

Solvent-free. Nonflammable. Requires no special protection or precautions in general use. Avoid prolonged contact with skin or contact with eyes.

Information for persons with allergies is available at +30 210 7793777 (Greece).

Disposal:

Dispose of empty packaging according to local regulations or recycle. Collect waste material, allow to dry out and harden and then dispose as Construction Waste.